

Features

- Low $R_{DS(on)}$
- Ultra-low Q_G For High Efficiency
- Logic Level
- Light Weight
- New Compact Die Adaptor Assembly
- Source Sense Pin
- Total Dose
 - Rated to 300 krad
- Single Event
 - SEE immunity for LET of 83.7 MeV/mg/cm² with V_{DS} up to 100% of rated Breakdown
- Low Dose Rate at 100 mRad/sec
 - Maintains Pre-Rad specification
- Neutron
 - Maintains Pre-Rad specification for up to 1×10^{13} Neutrons/cm²

Application

- Commercial Satellite EPS & Avionics
- Deep Space Probes
- High Speed Rad Hard DC-DC Conversion
- Rad Hard Motor Controllers

Thermal Characteristics

| Symbol | Parameter-Conditions | Value | Units |
|-----------------|---|-------|-------|
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient (Note 3) | 40 | °C/W |
| $R_{\theta JC}$ | Thermal Resistance Junction to Case | 9.8 | |

CDA04N08X2


**Rad Hard e-GaN® 40 V, 8 A,
16 mΩ Die Adaptor Product (CDA2)**

Description

EPC Space CDA series of eGaN® power switching HEMTs have been specifically designed for critical applications in the high reliability or commercial satellite space environments. These devices have exceptionally high electron mobility and a low temperature coefficient resulting in very low $R_{DS(on)}$ values. The lateral structure of the die provides for very low gate charge (Q_G) and extremely fast switching times. These features enable faster power supply switching frequencies resulting in higher power densities, higher efficiencies and more compact circuitry.

I/O Pin Assignment (Bottom View)

| Pin | Symbol | Description |
|-----|--------|--------------|
| 1 | G | Gate |
| 2 | D | Drain |
| 3 | SS | Source Sense |
| 4 | S | Source |



Absolute Maximum Rating ($T_C = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter-Conditions | Value | Units |
|----------------|--|-------------|-------|
| V_{DS} | Drain to Source Voltage (Note 1) | 40 | V |
| I_D | Continuous Drain Current I_D @ $V_{GS} = 5\text{ V}$, $T_C = 25^\circ\text{C}$, $R_{\theta JA} < 40^\circ\text{C/W}$ | 8 | A |
| I_{DM} | Single-Pulse Drain Current $t_{pulse} \leq 80\ \mu\text{s}$ | 32 | |
| V_{GS} | Gate to Source Voltage (Note 2) | +6 / -4 | V |
| T_J, T_{STG} | Operating and Storage Junction Temperature Range | -55 to +150 | °C |
| T_{sol} | Package Mounting Surface Temperature | 260 | |
| ESD | ESD Class | 1A | |

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted. Typical (TYP) values are for reference only.)

| Parameter | Symbol | Test Conditions | | MIN | TYP | MAX | Units |
|--|--------------------------|---|--------------------------------|-----|------|------|-------|
| Maximum Drain to Source Voltage | V _{DSMAX} | V _G = 0 V | | - | - | 40 | V |
| Drain to Source Leakage | I _{DSS} | V _{DS} = 40 V | T _C = 25°C | - | 10 | 100 | μA |
| | | V _{GS} = 0 V | T _C = 125°C | - | | 400 | |
| Gate to Source Forward Leakage | I _{GSS} | V _{GS} = 5 V | T _C = 25°C | - | 0.01 | 2 | mA |
| Gate to Source Reverse Leakage | I _{GSS} | V _{GS} = -4 V | T _C = 25°C | | -50 | -100 | μA |
| Gate to Source Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 2 mA | T _C = 25°C | 0.8 | 1.4 | 2.5 | V |
| Gate to Source Threshold Voltage Temperature Coefficient | ΔV _{GS(th)} /ΔT | V _{DS} = V _{GS} , I _D = 2 mA | -55°C < T _A < 125°C | - | 3.5 | - | mV/°C |
| Drain to Source Resistance (Note 4) | R _{DS(on)} | I _D = 8 A, V _{GS} = 3.5 V | T _C = 25°C | - | 14 | | mΩ |
| | | I _D = 8 A, V _{GS} = 5 V | T _C = 25°C | - | 13 | 16 | |
| Source to Drain Forward Voltage (Note 5) | V _{SD} | I _S = 1 A, V _G = 0 V | T _C = 25°C | | 2.0 | | V |

Dynamic Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted. Typical (TYP) values are for reference only.)

| Parameter | Symbol | Test Conditions | MIN | TYP | MAX | Units |
|---------------------------------|-----------|--|-----|-----|-----|----------|
| Input Capacitance | C_{ISS} | $f = 1\text{ MHz}$, $V_{DS} = 20\text{ V}$, $V_{GS} = 0\text{ V}$ (Note 6) | | 283 | 312 | pF |
| Output Capacitance | C_{OSS} | | | 170 | 270 | |
| Reverse Transfer Capacitance | C_{RSS} | | | 20 | 25 | |
| Gate Resistance | R_G | $f = 1\text{ MHz}$, $V_{DS} = V_{GS} = 0\text{ V}$ | | 0.4 | | Ω |
| Total Gate Charge (Note 7) | Q_G | $I_D = 4\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 2.2 | | nC |
| | | $I_D = 8\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 2.2 | 2.8 | |
| Gate to Drain Charge (Note 7) | Q_{GD} | $I_D = 4\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 0.1 | | |
| | | $I_D = 8\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 0.1 | 0.6 | |
| Gate to Source Charge (Note 7) | Q_{GS} | $I_D = 4\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 0.8 | | |
| | | $I_D = 8\text{ A}$, $V_{GS} = 5\text{ V}$, $V_{DS} = 20\text{ V}$ | | 0.8 | 1 | |
| Output Charge (Note 8) | Q_{OSS} | $V_{GS} = 0\text{ V}$, $V_{DS} = 20\text{ V}$ | | 6 | | |
| Source to Drain Recovery Charge | Q_{RR} | $I_D = 8\text{ A}$, $V_{DS} = 20\text{ V}$ | | <1 | | |

Radiation Characteristics

EPC Space eGaN[®] HEMTs are tested according to MIL-STD-750 Method 1019 for total ionizing dose validation. Every manufacturing lot is tested for total ionizing dose of Gamma radiation with an in-situ bias for (i) $V_{GS} = 5\text{ V}$, (ii) $V_{DS} = V_{GS} = 0\text{ V}$ and (iii) $V_{DS} = 80\% B_{VDSS}$.

Electrical Characteristics up to 300 krad ($T_C = 25^\circ\text{C}$ unless otherwise noted. Typical (TYP) values are for reference only.)

| Parameter | Symbol | Test Conditions | MIN | TYP | MAX | Units |
|-------------------------------------|--------------|--|-----|------|------|------------------|
| Maximum Drain to Source Voltage | V_{DSMAX} | $V_{GS} = 0\text{ V}$ | - | - | 40 | V |
| Gate to Source Threshold Voltage | $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D = 2\text{ mA}$ | 0.8 | 1.0 | 2.5 | V |
| Drain to Source Leakage | I_{DSS} | $V_{DS} = 40\text{ V}$, $V_{GS} = 0\text{ V}$ | - | 10 | 100 | μA |
| Gate to Source Forward Leakage | I_{GSS} | $V_{GS} = 5\text{ V}$ | - | 0.01 | 2 | mA |
| Gate to Source Reverse Leakage | I_{GSS} | $V_{GS} = -4\text{ V}$ | - | -10 | -100 | μA |
| Drain to Source Resistance (Note 4) | $R_{DS(on)}$ | $I_D = 8\text{ A}$, $V_{GS} = 5\text{ V}$ | - | 13 | 16 | $\text{m}\Omega$ |

Typical Single Event Effect Safe Operating Area

Note : All Single Event Effect testing is performed on the K-500 Cyclotron at Texas A&M University

| Test | | Environment | | | V_{DS} Voltage (V) | |
|---------|-----|-----------------------------|------------------------|------------------------|-----------------------|------------------------|
| See SOA | Ion | LET MeV/mg/cm^2 | Range μm | Energy MeV | $V_{GS} = 0\text{ V}$ | $V_{GS} = -4\text{ V}$ |
| | Xe | 50 | 131 | 1653 | 40 | 40 |
| | Au | 83.7 | 130 | 2482 | 40 | 40 |




Figure 1. Typical Single Event Effect Safe Operating Area




Figure 2. Typical Drain-Source Leakage Current vs. Ambient Temperature




Figure 3. Gate-Source Leakage Current vs. Ambient Temperature




Figure 4. Typical Gate-Drain Transfer Characteristic ($V_{DS} = 3$ V)




Figure 5. Typical Output Characteristics




Figure 6. Typical Drain-Source ON Resistance vs. Gate-Source Voltage vs. Ambient Temperature




Figure 7. Typical Drain-Source ON Resistance vs. Gate-Source Voltage vs. Drain Current




Figure 8. Typical Source-Drain Voltage vs. Temperature




Figure 9. Normalized Drain-Source ON Resistance vs. Ambient Temperature




Figure 10. Typical Inter-Electrode Capacitance vs. Drain-Source Voltage




Figure 11. Typical Gate Charge vs. Drain Current




Figure 12. Charge Test Circuit






Figure 13. Typical Gate Charge Test Waveform

Package Outline and Dimensions



| Symbol | Inches | Millimeters | Note |
|--------|--------|-------------|-----------|
| A | 0.047 | 1.193 | |
| B | 0.020 | 0.508 | |
| C | 0.028 | 0.711 | |
| D | 0.020 | 0.508 | |
| E | 0.008 | 0.203 | |
| F | 0.063 | 1.600 | |
| G | 0.016 | 0.406 | |
| H | 0.036 | 0.914 | |
| J | 0.015 | 0.381 | |
| K | 0.015 | 0.381 | |
| L | 0.047 | 1.194 | Ref. only |
| M | 0.091 | 2.311 | |
| N | 0.067 | 1.702 | |

CDA2 Footprint for Printed Circuit Board Design




| Symbol | Inches | Millimeters | Note |
|--------|--------|-------------|------|
| A | 0.051 | 1.295 | |
| B | 0.019 | 0.483 | |
| C | 0.008 | 0.203 | |
| D | 0.020 | 0.508 | |
| E | 0.032 | 0.813 | |
| F | 0.020 | 0.508 | |
| G | 0.024 | 0.610 | |
| H | 0.037 | 0.940 | |

Notes

- Note 1. NEVER exceed the absolute maximum V_{DS} of the device otherwise permanent damage/destruction may result.
- Note 2. NEVER exceed the absolute maximum V_{GS} of the device otherwise permanent damage/destruction may result. We recommend use at no greater than +5 V as the HEMT is fully conducting at this point.
- Note 3. $R_{\theta JA}$ measured with CDA1 package mounted to double-sided PCB, 0.063" thickness with 1.0 square inches of copper area on the top (mounting side) and a flood etch (3 square inches) on the bottom side.
- Note 4. Measured using four wire (Kelvin) sensing and pulse measurement techniques. Measurement pulse width is 80 μs and duty cycle is 1%, maximum.
- Note 5. With pulse measurement width 100–380 μs .
- Note 6. $C_{ISS} = C_{GS} + C_{GD}$ with C_{DS} shorted. $C_{OSS} = C_{DS} + C_{GD}$. $C_{RSS} = C_{GD}$.
- Note 7. The gate charge parameters are measured using the circuit shown in Figure 14. Qs and associated components BT1, P1 and C1 form a high speed current source that serves as the test load for the DUT. A constant gate current (I_{const}) of 1.5-3 mA is provided to the Gate of the DUT during the time that the ground switch (G_S) is OFF (t_{off}). The DUT is switched ON and OFF using ground-sensed switch GS. The gate current is adjusted to yield the desired charge per unit time ($I_{const} \cdot \text{time per division}$) on the measuring oscilloscope. The GS pulse drive ON time (t_{on}) is adjusted for the desired observability of the gate-source voltage (V_{GS}) waveform. The maximum duty cycle of the ground switch (t_{off}/t_{on}) should be set to 1% maximum. Please note that all gate-related signals are referenced to the "Source Sense" pin on the package. At all times during the measurement, the maximum gate-source voltage is clamped to 5 V_{DC} .
- Note 8. Guaranteed by design/device construction. Not tested.

EPC Space Part Number Information



Ordering Information Availability

| Screening Options | Rad Assurance Options |
|---|--|
| 1 character | 1 character |
| C = Developmental Unit V = Lite Screened | R = 100 krad, LET = 64 F = 300 krad, LET = 64 G = 500 krad, LET = 64 H = 1000 krad, LET = 64 Z = 1000 krad, LET = 84 |

| Part Number | Screening Level | Shipping |
|--------------|---------------------|--------------|
| CDA04N08X2*C | Engineering Samples | Waffle Trays |
| CDA04N08X2*S | Space Level | |

¹ Screening and qualification consistent to an equivalent MIL-PRF-19500 specification (KC).

C version CDA units are intended for engineering development purposes only and NOT supplied with radiation performance guarantees nor supplemental data packages

Data Package Order Detail
Consistent to MIL-PRF-19500 general specification

SPACE Screen

1. CDA04N08X2*S – OPTIONAL DATA PACKAGE

- A. Certificate of Compliance
- B. Serialization Records
- C. Preconditioning – Attributes Data Sheet (Lot Sample)
 - HTGB - Hi Temp Gate Stress Post Reverse Bias Data
 - HTRB - Hi Temp Drain Stress Post Reverse Bias Data
- D. Group A – Attributes Data Sheet
- E. Group B – Selected Mechanical Stress Test
- F. Group D – Attributes Data Sheet

Disclaimers

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE. EPC Space Corporation, its affiliates, agents, employees, and all persons acting on its or their behalf (collectively, "EPC Space"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. EPC Space makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose. To the maximum extent permitted by applicable law, EPC Space disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on EPC Space market knowledge of typical requirements that are often placed on similar technologies in generic applications. Product specifications do not expand or otherwise modify EPC Space terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, EPC Space products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the EPC Space product could result in personal injury or death. Customers using EPC Space products not expressly indicated for use in such applications do so at their own risk. Please contact authorized EPC Space personnel to obtain written terms and conditions regarding products designed for such applications. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of EPC Space. Product names and markings noted herein may be trademarks of their respective owners.

Export Administration Regulations (EAR)

The products described in this datasheet are subject to the U.S. Export Administration Regulations (EAR), 15 C.F.R. Pts 730-774, and are classified in ECCN 9A515.e. These products may not be exported, reexported, or transferred (in country) to any foreign country, or foreign entity, by any means, except in accordance with the requirements of such regulations.

Patents

EPC Corporation and EPC Space hold numerous worldwide patents. Any that apply to the product(s) listed in this document are identified by markings on the product(s) or on internal components of the product(s) in accordance with local patent laws.

eGaN[®] is a registered trademark of Efficient Power Conversion Corporation, Inc. Data and specification subject to change without notice.

Revisions

| Datasheet Revision | Product Status |
|--------------------|------------------------------------|
| REV P# | Proposal/development |
| REV Q# | Characterization and Qualification |
| M-701-001-D | Production Released |

Information subject to change without notice.

Revised November, 2020